Technical data sheet

Universal counter-trough, plastic

Item number: 1198022





Regardless of the type of rail, the counter-trough can be used by applying it onto one side of the clamp clip. Due to an intelligent contour on the backside, the counter-trough can be combined to a double trough. Retrofitting possible without the need to dismantle.



Polypropylene

B.4			-4-
IVI	aste	ar u	ala

Item number	1198022
Туре	2058UW 22 LGR
Description 1	Counter-trough
Description 2	combinable with double trough
Available from	15.05.2019
Manufacturer	OBO
Dimension	16-22mm
Colour	Light grey; RAL 7035
Material	Polypropylene
Smallest sales unit	100
Unit of quantity	Piece
Weight	0.268 kg
Weight unit	kg/100 pc.


Technical data sheet

Universal counter-trough, plastic


Item number: 1198022



Dimensions



Dimension B	27.5 mm
Dimension H	6.8 mm
Dimension L	37 mm



Technical data

Counter-trough/clip version	Counter sleeve
Suitable for max, cable diameter	22 mm
Cultubio for max. Cubic diamotor	ZZ TIIII
Clamping range D, max.	22 mm
Clamping range D, Max.	22
01 ' D '	10
Clamping range D, min.	16 mm
1 3 - 3 - 7	