

Technical data sheet

AXIS Maxi windowsill trunking, trunking width 130

Item number: 6131076



AXIS Maxi windowsill trunking for covered cable routing in interiors and for device installation.
Trunking base with symmetrical base perforation for direct mounting on the wall.
Tested to DIN EN 50085-1 and DIN EN 50085-2-1.
Base with enclosed cable retaining clips, cover included.



PVC Polyvinylchloride

Master data	
Item number	6131076
Description 1	Cable trunking
Description 2	AXIS MAXI Set 65x130 9010
Manufacturer	OBO
Colour	Pure white; RAL 9010
Material	Polyvinylchloride
Smallest sales unit	16
Unit of quantity	Metre
Weight	148 kg
Weight unit	kg/100 m
CO Footprint (GWP) Cradle-to-Gate	2,786 kg COe / 1 Meter


Technical data sheet

AXIS Maxi windowsill trunking, trunking width 130

Item number: 6131076



Dimensions



Length	2,000 mm
Width	130 mm
Height	65 mm

Technical data

Number of fixed partitions	0
Number of cables NYM 3 x 2.5 mm ² Ø 11.5 mm (without socket)	29
Number of insertable partitions	1
Version, cable trunking cover	Loose
Fastening type	Base perforation
Halogen-free	no
Cable retaining clip	yes
Duct connector	no
Usable cross-section	6800 mm ²
Protection rating	IP40
Protective film	no
Protection rating IK code	IK08
Permitted temperature range, max.	60 °C
Permitted temperature range, min.	-5 °C