### **Technical data sheet**

### PYROPLUG® MagicBox, four-sided, interior height 60 mm



**Item number: 7204012** 



Fire protection box as an insulation system, made of two-part stainless steel housing with intumescent fire protection inlays. Can be used in walls and ceilings. Quick mounting through the releasable Magic connection. Interior can be fully assigned with installations. For interior application. Closure of the residual openings with PYROSIT® NG fire protection foam, particularly simple for difficult geometries. CE-labelled construction product with general type approval. Fire resistance class El90 (fire-resistant). Including graphite strip.

### (€

A2

Stainless steel

2B

Bright, treated

#### Master data

| Item number         | 7204012                     |
|---------------------|-----------------------------|
| Туре                | PMB 640-4 A2                |
| Description 1       | Fire Protection Box 4-sided |
| Description 2       | with intumescending inlays  |
| Available from      | 04.10.2022                  |
| Manufacturer        | OBO                         |
| Dimension           | 300x423x130                 |
| Colour              | stainless steel             |
| Material            | Stainless steel             |
| Surface             | Bright, treated             |
| Surface standard    |                             |
| Smallest sales unit | 1                           |
| Unit of quantity    | Piece                       |
| Weight              | 563.1 kg                    |
| Weight unit         | kg/100 pc.                  |
|                     |                             |

# **Technical data sheet**

# PYROPLUG® MagicBox, four-sided, interior height 60 mm



**Item number: 7204012** 



|  |  | ca |  |  |  |
|--|--|----|--|--|--|
|  |  |    |  |  |  |
|  |  |    |  |  |  |

| Fire protection version | Box body    |
|-------------------------|-------------|
| Shape                   | Rectangular |
| Accessories required    | yes         |
| Internal height         | 64 mm       |
| Internal width          | 405 mm      |