## **Technical data sheet**

Bend, angle-adjustable, 60 A2

Item number: 6037162



Angle-adjustable bend for the creation of a horizontal branch, fitting for lock and screw-on cable trays of side height 60 mm. Adjustable angle 0–90°. Screwless mounting with double clamps or screw connection with FRS truss-head screws and M6 combination nuts. Can be used indoors and outdoors. Fastening material must be ordered separately.

# CERK

A2

Stainless steel

2E

Bright, treated

#### Master data

Item number	6037162	
Туре	RB W 660 A2	
Description 1	Adjustable bend	
Description 2	horizontal	
Manufacturer	OBO	
Dimension	60x600	
Colour	stainless steel	
Material	Stainless steel 1.4301	
Surface	Bright, treated	
Surface standard		
Smallest sales unit	1	
Unit of quantity	Piece	
Weight	405.8 kg	
Weight unit	kg/100 pc.	
CO2 Footprint (GWP) Cradle-to- Gate	48,1341 kg CO2e / 1 Piece	

# **Technical data sheet**

## Bend, angle-adjustable, 60 A2

**Item number: 6037162** 



#### Dimensions



Width	600 mm
Height	60 mm
Plate thickness	1.25 mm
Dimension B	600 mm
Dimension L	1,050 mm

Technical data		
	Bend (angle)	Adjustable
	Connector version	Integrated connector
	Туре	Adjustable bend_complete
	Maintain electrical functions	no
	Material thickness, floor plate	1.25 mm
	With cover	no
	Mounting perforation in base	yes
	NATO hole pattern	no
	Change of direction	Horizontal
	Rustproof steel, pickled	no
	Side perforation	yes
	Permitted temperature range, max.	120 °C
	Permitted temperature range, min.	-20 °C
	Wide-span version	no
	Type of connector, cable support system	screwed/clamped
	Recommended quantity of bolts	16 St.
	Rail thickness	1.25 mm