Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 28 mm

Item number: 7400287



Underfloor duct (2 piece) for routing cables in screed-covered underfloor systems, according to EN 50085-2-2. Removable and continuously lockable trunking cover. With separating retainers in the trunking base. Maximum load-bearing capacity to 1.5 kN.
The profiled side walls offer a locking mechanism to lock the duct cover onto the duct base. The stiffening beads in the duct cover serve to create stability.

St Steel

FS Strip galvanised

Master data


Item number	7400287
Type	S3 35028-2
Description 1	Underfloor duct, 2-part
Description 2	3 compartments
Manufacturer	OBO
Dimension	2000x350x28
Material	Steel
Surface	Strip galvanised
Surface standard	DIN EN 10346
Smallest sales unit	2
Unit of quantity	Metre
Weight	503.717 kg
Weight unit	kg/100 m
CO2 Footprint (GWP) Cradle-to-Gate	11,244 kg CO2e / 1 Meter

Technical data sheet

Underfloor duct, 2 pieces, 3-compartment, duct height 28 mm

Item number: 7400287

Dimensions



Length	2,000 mm
Width	350 mm
Height	28 mm
Dimension a	120 mm
Dimension b	110 mm
Dimension h	28 mm

Technical data

Number of fixed partitions	2
Number of compartments	3 St.
Mounting system fastening type	Floor
Floor plate	yes
Application area	Screed-covered
Decouplable	no
Trunking width, min.	350 mm
Duct height, min.	28 mm
Usable cross-section	8722 mm²
Removable cover	yes
Cross-section, draw a	2944 mm²
Cross-section, draw b	2834 mm²
ROHS-conformant	yes
Vertical load, large area	to 1,500 N